




OPGW Cable Specifications

T G G

Cable Type: OPGW - 2S 2 / 24+12 (M105 / R71 - 107)

Cross Section:



Fiber type: 36xG.652D

Design:			
	Name	No	Material Dia.
Center	20%ACSwire	1	2.90 mm
	20%ACSwire	4	2.80 mm
Layer1	AA(LHA2)wire	0	
	SUS Tube	2 / 24+12	2.70 mm
Layer2	20%ACSwire	2	2.80 mm
	AA(LHA2)wire	10	

Stranded:core and layer1 greased	
stranding direction of outer layer is "right" hand(Z-stranding)	
Cable Diameter	14.10 mm
Cable Weight	501 kg/km

Technical Data:	according to: IEEE 1138 standards	
Supporting Cross Section	105.13 mm ²	
Section of ACS Wire / AA Wire	43.55 / 61.58 mm ²	
Rate Tensile Strength (RTS)	70.7 kN	
Modulus of Elasticity (E-Modulus)	105.2 kN/mm ²	
Thermal Elongation Coefficient	16.6 10 ⁻⁶ /°C	
Permissible Maximum Working Stress(MAT) (40%RTS)	269.0 N/mm ²	
Everyday Stress (EDS) (16%~25%RTS)	107.6	~ 168.1 N/mm ²
Strain Margin Stress (60%RTS)	403.4 N/mm ²	
DC Resistance (20 °C)	0.423 Ω / km	
Short Circuit Current (1s, 20°C~200°C)	10.35 kA	
Short Circuit Current Capacity (20°C~200°C) (I _{2t})	107.16 kA ² s	
Minimum Bending Radius (installation)	≥ 353 mm	
Installation Tensile Strength (≤20%RTS)	≤14.1 kN	
Temperature Range:	Installation	-10°C ~ +50 °C
	Transportation and Operation	-40°C ~ +80 °C

Remarks: All Sizes and Values are Nominal Values

2 / 24+12 - Tubes / Fibers of Tube

M105 - Supporting Cross Section

R71 - Rate Tensile Strength (RTS)

107 - Short Circuit Current Capacity (20°C~200°C)

2018/8/7		OPGW	zjm_No:39N Cathy
----------	--	------	--------------------